

BLANK PAGE



Indian Standard SPECIFICATION FOR CAST IRON ROLLS

(First Reprint MARCH 1982)

UDC 669.13-122



Copyright 1972

INDIAN STANDARDS INSTITUTION
MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

NEW DELHI 110002

Price Rs 5.00

Gr

2

December 1972

Indian Standard

SPECIFICATION FOR CAST IRON ROLLS

Cast Iron and Malleable Cast Iron Sectional Committee, SMDC 9

Chairman

Representing

DR PRANLAL PATEL

Malleable Iron & Steel Castings Co Pvt Ltd, Bombay

Members

Electrosteel Castings Ltd, Calcutta SHRIS. N. AGRAWAL

SHRIS, S. CHAWDHURY (Alternate)

DR S. N. ANANT NARAIN

International Nickel (India) Pvt Ltd, Bombay Mining and Allied Machinery Corporation Ltd, SHRI M. ANJANEYULU Durgapur

SHRI B. M. SENGUPTA (Alternate)

SHRI N. C. BAGCHI SHRI R. M. BALANI National Test House, Calcutta Directorate General of Technical Development (Ministry of Industrial Development), New Delhi

SHRI T. R. MOHAN RAO (Alternate)

SHRI B. N. BALIGA

Premier Automobiles Ltd (Mechanite Foundry), Bombay

CHEMIST & METALLURGIST, Ministry of Railways

CHITTARANJAN LOCOMOTIVE

WORKS, CHITTARANJAN

ASSISTANT DIRECTOR (MET)-II, RESEARCH, DESIGNS & STANDARDS

ORGANIZATION, LUCKNOW (Alternate)

In personal capacity (164, Sector 27-A, Chandigarh) SHRI M. S. DUA

EXECUTIVE ENGINEER, CENTRAL Central Public Works Department, New Delhi

STORES DIVISION NO. I

SHRI P. C. GUPTA

SHRI P. R. JALAN SHRI L. M. JOSHI

SHRI B. K. GIRI (Alternate)

SHRI P. L. KATHURIA

SHRI M. C. AICH (Alternate)

SHRI B. V. MAHABALE

SHRI M. S. DESHPANDE (Alternate)

SHRI M. P. MANIVANNAN

SHRI Y. M. MEHTA SHRI R. C. KOTHARI (Alternate)

Hindustan Shipyard Ltd, Visakhapatnam Hindustan Malleables & Forgings Ltd, Dhanbad Tata Engineering and Locomotive Co Ltd. Iamshedpur

Directorate General of Supplies & Disposals (Inspection Wing), New Delhi

New Precision (India) Pvt Ltd, Dewas

Cast Iron Spun Pipes Manufacturers Association, Pioneer Equipment Co Pvt Ltd, Baroda

(Continued on page 2)

INDIAN STANDARDS INSTITUTION

MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG

(Continued from page 1)

Members

SHRIN D. MIMANI SHRI AMAL MITRA

SHRI A. GUHA (Alternate)

SHRI B. MUKHERJEE

SHRI S. K. MOULIK (Alternate)

SHRI P. C. NEOGY SHRI J. MOHAN (Alternate) SHRI A. K. POLEY

SHRI B. K. DHAR CHOWDHURY (Alternate)

SHRIB. V. PRABBU

SHRI J. S. TRIPATHI (Alternate) SHRIS R. RAMACHANDRAN

SHRI R. K. SINHA (Alternate)

SHRI V. R. REDDY REPRESENTATIVE

SHRI C. SANJEEVI

SHRI M. P. MANIVANNAN (Alternate) SHRI C. S. S. SETTY

SHRI K. V. RAMAKRISHNAN (Alternate)

SHRI AMOLAKH S. SHARDA

SHRI RAVINDRA R. Row (Alternate) SHRI K. N. SHARMA

SHRI R. R. JOSHI (Alternate)

SHRIS M. R. SINGH

SHRI J. B. SAXENA (Alternate)

SHRI S. G. TILLU DR S. K. TIWARY

SHRI H. VINOD

SHRI G. V. YAGNAVALKYA

SHRI F. S. KATPITIA (Alternate) SHRI R. K. SRIVASTAVA, Deputy Director (Struc & Met)

(Secretary)

Representing

Sree Engineering Products Ltd. Rishra Institute of Indian Foundrymen, Calcutta

Burn & Co Ltd, Howrah

Indian Iron & Steel Co Ltd, Calcutta

Shiva Durga Iron Works (P) Ltd, Howrah

Heavy Engineering Corporation Ltd. Foundry Forge Plant, Ranchi

Fertilizer Corporation of India Ltd. Sindri

Bharat Heavy Electricals Ltd, Tiruchirapalli Co-ordinating Committee on Materials for Auto-

mobiles, SMDC 31, ISI

Sakthi Pipes Ltd, Madras

Ennore Foundries Ltd. Madras

R. M. Engineering Works, Ahmedabad

Kesoram Spun Pipes & Foundries, Calcutta

Directorate General of Ordnance Factories (Ministy of Defence), Calcutta

Indian Smelting & Refining Co Ltd, Thana

National Metallurgical Laboratory (CSIR). Jamshedpur

Oil and Natural Gas Commission, Dehra Dun

Jyoti Ltd, Baroda

Director General, ISI (Ex-officio Member)

Panel for Cast Iron Rolls, SMDC 9: P 6

Convener

SHRI R. C. PROSAD

Heavy Engineering Corporation Ltd, Foundry Forge Plant, Ranchi

Members

SHRI H. K. NATHANI SHRI H. P. RAY

Gontermann-Peipers (India) Ltd, Calcutta Tata-Yodogawa Ltd. Jamshedour

AMENDMENT NO. 1 NOVEMBER 2012 TO IS 6629 · 1972 SPECIFICATION FOR CAST

IS 6629: 1972 SPECIFICATION FOR CAST IRON ROLLS

(*Page* 4, *clause* **6.1**) — Insert the following at end of clause:

'd) High hardness (clean chill and D.P.) rolls to be mirror-finished.'

[Page 6, Table 1, Sl No. (iv)] — Insert the following new Grade and Hardness of Barrel, Shore 'C' Scale.

'S.G. (Acicular) — 65-80'

(Page 6, clause 11.1) — Insert the following after the first sentence.

'Roll end face should also indicate drive end and non-drive end.'

(MTD 6)

Indian Standard SPECIFICATION FOR CAST IRON ROLLS

0. FOREWORD

- 0.1 This Indian Standard was adopted by the Indian Standards Institution on 12 October 1972, after the draft finalized by the Cast Iron and Malleable Cast Iron Sectional Committee had been approved by the Structural and Metals Division Council.
- **0.2** This standard covers the requirements for cast iron rolls. A wide range of compositions is used to obtain the desired characteristics in cast iron rolls, such as hardness, toughness, resistance to spalling and heat, hardness-gradient and grain structure.
- 0.3 For information of the users, general description of the various types of rolls included in this standard is given in Appendix A.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS: 2-1960*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

1. SCOPE

1.1 This standard covers the requirements of cast iron rolls for metallurgical industries.

2. SUPPLY OF MATERIAL

2.1 General requirements relating to the supply of material shall be as laid down in IS: 1387-1967†.

3. GRADES

- 3.1 There shall be five types of cast iron rolls, namely:
 - a) Clear chill rolls (C. C.).
 - b) Indefinite chill rolls (I.C.),

^{*}Rules for rounding off numerical values (revised).

[†]General requirements for supply of metallurgical materials (first revision).

IS: 6629 - 1972

- c) Grain iron rolls (G. I.).
- d) S. G. iron rolls, and
- e) Double poured rolls:
 - i) High alloy (D. P.),
 - ii) High alloy/S. G. Core (D. P. S.).
- 3.2 Each type of cast iron rolls shall have various grades as specified below:

Туре	Grade
a) Clear chill rolls	C. C. I, C. C. II, C. C. III, C. C. IV
b) Indefinite chill rolls	I. C. I, I. C. II, I. C. III
c) Grain iron rolls	G. I. I, G. I. II
d) S. G. iron rolls	S. G. I, S. G. II, S. G. III
e) Double poured rolls:	
i) High alloy	D. P. I, D. P. II, D. P. III, D. P. IV

ii) High alloy/S. G. core

D. P. S. I, D. P. S. II, D. P. S. III, D. P. S. IV

4. MANUFACTURE

4.1 Unless otherwise agreed to between the purchaser and the manufacturer, the method of manufacture and heat-treatment shall be left to the discretion of the manufacturer.

5. CHEMICAL COMPOSITION

5.1 Unless otherwise agreed to between the purchaser and the manufacturer the chemical composition shall be left to the discretion of the manufacturer.

6. FINISH

- 6.1 Rolls shall be supplied in any one of the following conditions as agreed to between the purchaser and the manufacturer:
 - a) Neck to be either machine-finished or ground-finished as required;
 - b) Wobbler to be machine-finished or as cast as required; and
 - c) Barrel to be rough-finished, smooth-finished or ground-finished as required by the customer, except for the barrel of the grooved rolls, which shall be supplied in rough-finished condition.

7. TOLERANCES

7.1 Tolerance on size shall be specified in the order or on the drawings. If nothing is specified, these shall be as follows:

Neck \pm 0.75 mmWobbler \pm 2 mmBarrel diameter \pm 1 percent

7.2 Tolerance on the length of neck, wobbler and barrel shall be as specified on the drawings supplied by the purchaser or as mutually agreed to between the manufacturer and the purchaser.

8. FREEDOM FROM DEFECTS

- 8.1 Working surfaces of barrel and journal of machine finished rolls shall be free from surface defects. However, minor defects may be rectified or left as such as agreed to between the purchaser and the manufacturer.
- 8.1.1 Minor defects shall be permitted on the non-working surfaces of all rolls.

9. HARDNESS TEST

- 9.1 Each roll shall be tested for hardness and shall be within the limits specified in Table 1. The hardness shall be measured on the barrel surface. The stage of processing where hardness test is conducted and the number and location of tests may be as agreed to between the purchaser and the manufacturer. A sufficient number of hardness tests shall be made to ensure required uniformity, both longitudinally and circumferentially.
- 9.2 Hardness values shall be determined preferably by Shore 'C' scleroscope.

10. CHILL DEPTH

10.1 Chill depth for clear chill rolls shall be as agreed to between the purchaser and the manufacturer.

NOTE — Chill depth is the distance from the machined surface to the depth where three or more first graphite points are visible by the naked eye on a 10 mm long line perpendicular to the radius. Other individual graphite points are not to be taken into consideration.

10.2 Chill depth shall be measured at the end face of the barrel.

TABLE 1 CLASSIFICATION OF CAST IRON ROLLS

(Clause 9.1)

SL No.	Туре	GRADE	HARDNESS OF BARREL SHORE 'C' SCALE
i)	Clear chill rolls (alloyed or unalloyed)	C. C. I C. C. II C. C. III	58- 65 65-70 70-75
ii)	Indefinite chill rolls	I. C. I I. C. II I. C. III	45-55 55-65 65-75
iii)	Grain iron rolls	G. I. I G. I. II	30-40 40-50
iv)	S. G. iron rolls	S. G. I S. G. II	45-55 55-65
v)	Double poured rolls:		
•	a) High alloy	D. P. I D. P. II D. P. III D. P. IV	65-70 7 0- 75 75-80 80-90
	b) High alloy/S. G. core	D. P. S. I D. P. S. II D. P. S. III D. P. S. IV	65-70 70-75 75-80 80- 90

11. MARKING AND PACKING

11.1 Roll numbers shall be marked on both the end faces of the wobblers. The manufacturer's name or trade-mark shall also be indicated at one of the end faces. Each roll shall be suitably packed to ensure delivery in desired condition as required by the customer.

11.1.1 The material may also be marked with the ISI Certification Mark.

Note — The use of the ISI Certification Mark is governed by the provisions of the Indian Standards Institution (Certification Marks) Act and the Rules and Regulations made thereunder. The ISI Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well-defined system of inspection, testing and quality control which is devised and supervised by ISI and operated by the producer. ISI marked products are also continuously checked by ISI for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the ISI Certification Mark may be granted to manufacturers or processors; may be obtained from the Indian Standards Institution.

11.2 Packing—Each roll shall be suitably packed to ensure delivery in good condition.

APPENDIX A

(Clause 0.3)

GENERAL DESCRIPTION OF CAST IRON ROLLS

A-1. CLEAR CHILL ROLLS

- A-1.1 Clear chill rolls have the following three working zones:
 - a) Clear Chill Zone Comprises of metallic matrix and carbide without showing any mecrographite,
 - b) Mottled Zone Transition zone between clear chill zone and grey core, in which carbide content decreases continuously with corresponding increase in graphite towards the core, and
 - c) Grey Zone Comprises of grey iron.

A-2. INDEFINITE CHILL ROLLS

A-2.1 The working layer of indefinite chill rolls comprises of metallic matrix, carbide in radial form with fine flake graphite dispersed in between the carbide. The quantity of graphite increases from the surface to the core.

A-3. GRAIN IRON ROLLS

A-3.1 Working layer of grain iron rolls comprises of metallic matrix, graphite with or without some quantity of free carbide.

A-4. S. G. IRON ROLLS

A-4.1 S. G. iron rolls comprise of matallic matrix, carbide and graphite nodules.

A-5. DOUBLE POURED ROLLS

A-5.1 In double poured rolls, the core of the roll is usually comprised of soft grey iron, but rolls exposed to high mechanical stress require spheroidal graphite material.

INTERNATIONAL SYSTEM OF UNITS (SI UNITS)

5-8-56C L. N. Gupta Marg

117/418 B Sarvodaya Nagar

Patliputra Industrial Estate

D-277 Todarmal Marg, Banipark

Hantex Bldg (2nd Floor), Rly Station Road

Quantity	Unit	Symbol	
Length	metre	m	
Mass	kilogram	kg	
Time	second	8	
Electric current	ampere	A	
Thermodynamic temperature	kelvin	K	
Luminous intensity	candela	cd	
Amount of substance	mole	mol	
Supplementary Units			
Quantity	Unit	Symbol	
Plane angle	radian	rad	
Solid angle	steradian	ST	
Derived Units			
Quantity	Unit	Symbol	Conversion
Force	newton	N	1 N = 1 kg.1 m/s*
Energy	joule	3	1 J-1N.m
Power	watt	W	1 W = 1 J/s
Flux	weber	Wb	1 Wb - 1 V.s
Flux density	tesla	T	1 T = 1 Wb/m2
Frequency	hertz	Hz	1 Hz - 1 c/s (s-1)
Electric conductance	siemens	S	1 S=1 A/V
Pressure, stress	pascal	Pa	1 Pa = 1 N/m1
INDIAN STANDARDS	INSTITUTION		
Manak Bhavan, 9 Bahadu		EW DELHI	110002
Telephones : 26 60 21,	27 01 31	Tele	grams : Manaksanstha
Regional Offices:			Telephone
Western : Novelty Cham		BOMBAY	
Eastern : 5 Chowringhee Approach		CALCUTTA 700072 23-08 02	
Southern : C. I. T. Camp	ous, Adyar	MADRAS	
Branch Offices:			
'Pushpak', Nurmohamed S	The state of the s	AHMADAI	BAD 380001 2 03 91
'F' Block, Unity Bldg, Nari		BANGALO	
Gangotri Complex, Bhadbl	hada Road, T.T. Nagar	BHOPAL 4	
22E Kalpana Area			SHWAR 751014 5 36 27
Ahimsa Bldg, SCO 82-83,	Sector 17C	CHANDIG	ARH 160017 2 83 20
CONTRACT IN COLUMN SERVICE	THE RESERVE OF THE PARTY OF THE	A STATE OF THE PARTY OF THE PAR	THE RESERVE OF THE PARTY OF THE

HYDERABAD 500001

TRIVANDRUM 695001

JAIPUR 302006

KANPUR 208005

PATNA 800013

22 10 83

6 98 32

8 12 72

6 28 08

32 27